Large Woody Debris and Engineered Logjams

Tim Abbe Herrera Environmental Consultants, Inc.



Herrera Environmental Consultants

Some basic guidelines for building a sound foundation for sustained rehabilitation of fluvial ecosystems:

- 1. Know how physical elements and processes have changed and their significance to the system.
- 2. Re-introduce or emulate the key elements which have been lost.
- 3. Understand the consequences of "restoring" natural systems, particularly w.r.t. human development.
- 4. Adapt land management and infrastructure to accommodate recovery of disturbance regimes that sustain ecological communities.







"Engineered" Logjams Means They are Carefully Analyzed and Designed for a Factor of Safety and a Specified Design Life

- Size, position, and spacing of ELJs based on:
 - Hydraulic analysis of flow behavior near structure(s)
 - Channel response over time
- ELJ architecture & materials based on:
 - Scour analysis
 - Structural stability analysis
 - Material design life analysis
- All structures designed to emulate nature and provide maximum possible benefits to restoring native habitat

2

6

Engineered Logjam Design Process

1 Reach Analysis

- Fluvial geomorphology
- Hydrology & hydraulics
- Ecology/Habitat/ESA
- Wood & sediment budgets

Risk Assessment

- Risk to habitat and humans
- Factor of Safety
- Engineering Analysis
- System Response

Construction

5

- Materials (trees)
- Access and sequencing
- Flow diversion and de-watering
- Erosion and water quality

Feasibility


- Opportunities/Constraints
- Stakeholder concerns
- Design Alternatives
- Acceptable Risk and Cost
- Cost Benefit

Design

- Type of structure and architecture
- Number of structures, size, location
- Force balance
- Scour and deposition
- Channel dynamics

Inspection Monitoring

- Culling or repair
- Re-vegetation
- Accumulation/Loss of ballast
- Flotsam accumulation



Herrera Environmental Consultants






Herrera Environmental Consultants


Tim Abbe, June 15, 2006





Species richness increases in rivers with the addition of logjams




Pess et al. 2002









Logjams also make great habitat for *Homo Sapiens*




Herrera Environmental Consultants

The Many Types of ELJ Projects:

 Bank roughening Bank stabilization Flow deflection •Flow bifurcation Grade control

Tim Abbe, June 15, 2006



Smooth shoreline:

High velocity flowline hugs shoreline where there is lack of boundary roughness provided by woody vegetation and channel shoreline is subjected to shear stresses.





Rough shoreline:

High velocity flowline is offset by boundary roughness provided by woody vegetation, reducing shear stress along the channel shoreline.



Natural Bank Roughening



Chilkat River, Klukwan, Alaska



Herrera Environmental Consultants

Flow Deflection

Tim Abbe, June 15, 2006





Engineered logjam constructed in 1999 to protect Forest Road 23, Cispus River. November 2004.

Herrera Environmental Consultants

Evaluating Design Principles – Examples from Actual Projects:


Williams River, NSW, Australia














Herrera Environmental Consultants

North Fork Stillaguamish Project

ELJ Functions – Hard Point Flow Deflectors






1998



Herrera Environmental Consultants







Herrera Environmental Consultants



2001



Herrera Environmental Consultants







Herrera Environmental Consultants








Herrera Environmental Consultants



1998




Herrera Environmental Consultants



1999


Tim Abbe, June 15, 2006



2000




Herrera Environmental Consultants



2001



Herrera Environmental Consultants



2004



Herrera Environmental Consultants

ELJ no.2



2005



ELJ no.2



2001

3 years after construction, ELJ 2 with racked woody debris and only tips of key member rootwads visible. Main channel has split into 2 channels around the ELJ.



2005

7 years after construction, a significant decrease in racked woody debris has occurred and key member rootwads are much more visible. Main channel flowing entirely to left of ELJ.

ELJ no.3



1998



Herrera Environmental Consultants





1999



Herrera Environmental Consultants

ELJ no.3







Herrera Environmental Consultants







Herrera Environmental Consultants







Herrera Environmental Consultants



Note pitch of broken log: downstream tip is pointed down

ELJ no.3

2004



Herrera Environmental Consultants




Note that pitch of broken log has reversed, with downstream tip pointed up, indicated upstream corner of structure has settled (~1 m) due to undercutting scour. 2005



Herrera Environmental Consultants


ELJ no.3




North Fork Stillaguamish ELJ #1, Log #5

Herrera Environmental Consultants

Effect of Scour on Structural Integrity: Logs sink Plan



1999 Profile (after 8 overbank flow events)




North Fork Stillaguamish ELJ #1, Log #5

Tim Abbe, June 15, 2006

The Hoh River Project

Tim Abbe, June 15, 2006


The Hoh River moves at rates up to 30 m/yr (100 ft/yr)



Tim Abbe, June 15, 2006

"Natural Analogs"

The Hoh River at Nolan Creek provides a current analog for Hoh Project concept of "chute" meander cut-off:



March 29, 2004



Herrera Environmental Consultants

Major Project Elements

Mid-channel logjams (4)

Flow

Diversion channel


Bank logjams (8)

Sediment retention area




Herrera Environmental Consultants

Hoh project objective: get river away from Highway 101




Tim Abbe, June 15, 2006

Depth averaged velocity (ft/s) output from FESWMS for existing conditions during 100 yr peak flow event (67,000 cfs)




Tim Abbe, June 15, 2006

Depth averaged velocity (ft/s) output from FESWMS for proposed conditions during 100 yr peak flow event (67,000 cfs)



Tim Abbe, June 15, 2006

Mid-channel ELJ plan and section view



Almost done, October 2004






Hoh River project site in Spring of 2004 prior to construction.



Herrera Environmental Consultants



Hoh project site design layout



Tim Abbe, June 15, 2006



Herrera concept figure of how we predicted the project site would look in 2005.






Hoh project site as-built conditions in October 2004.



Herrera Environmental Consultants



Hoh project site 12-15-04, after a 30,000 cfs peak flow (~2 yr recurrence interval).





Hoh project site 02-01-05, after two peak flows of ~30,000 cfs.



South Fork Tolt

Tim Abbe, June 15, 2006





Herrera Environmental Consultants

Tim Abbe, June 15, 2006



Tim Abbe, June 15, 2006




Tim Abbe, June 15, 2006




Tim Abbe, June 15, 2006






Floodplain Reconnection of Lower Tolt River Delta




Tim Abbe, June 15, 2006






Herrera Environmental Consultants


Existing Erosion (2-yr flood)






Tim Abbe, June 15, 2006


Existing Erosion (10-yr Flood)



Tim Abbe, June 15, 2006


Levee Removal Erosion (2-yr flood)






Tim Abbe, June 15, 2006

Erosion over time (10-yr Flood)




Tim Abbe, June 15, 2006


Yakima Basin Aquatic Science and Management Conference





Basis of ELJ Design



Herrera Environmental Consultants







Herrera Environmental Consultants

Mendenhall River, Juneau, Alaska: A simple log crib revetment




Tim Abbe, June 15, 2006

Complex ELJ Bank Crib – Mendenhall River, Juneau, Alaska, 2006



Complex ELJ Bank Crib – Mendenhall River, Juneau, Alaska, 2006







Tim Abbe, June 15, 2006

Complex ELJ Bank Crib – Mendenhall River, Juneau, Alaska, 2006





Tim Abbe, June 15, 2006



Tim Abbe, June 15, 2006



Tim Abbe, June 15, 2006

